



**Make : New Way Electronics
Model No : NWE-PTP-II**

Overview:

THE BLUETOOTH IMPACT PRINTER IS IDEAL FOR LONG-TERM DURATION (NON-FADING, INK BASED PRINTS) OF RECEIPTS/DOCUMENTS. IT IS COMPATIBLE WITH ANY ANDROID DEVICE VIA BLUETOOTH/USB. IT IS USER PROGRAMMABLE AND COMES WITH SDK THAT HELPS IN DEPLOYMENT OF CUSTOM APPLICATIONS.IT WORKS FOR MORE THAN 10 HOURS WITH INTERNAL BATTERY.



FEATURES:

- 1. PUSH-BUTTON START**
- 2. WATERPROOF AND DUSTPROOF LEVEL: IP54, STILL WORK IN RAINY OUTDOOR**
- 3. ANTI-THROW CAPACITY CAN REACH: 1.2M (CEMENT FLOOR)**
- 4. SUPPORT ONE DIMENSIONAL BARCODE PRINTING, ALSO SUPPORT TWO DIMENSIONAL BARCODE LIKE QR CODE, PDF 417**
- 5. 7.4V/2600MAH LARGE CAPACITY BATTERY WITH POWER SAVING DESIGN, EXTENSION USE**
- 6. INTERFACE: BLUETOOTH 4.0 & BLE SUPPORT/WI-FI/RS232/MINI USB/**
- 7. SUPPORT BLUETOOTH SUPERIOR FUNCTION, ALSO SUPPORT VARIOUS BLANK AND PRE-PRINTING TICKET PRINTING**
- 8. STQC CERTIFIED L1 BIO-METRICS SCANNER**

APPLICATIONS:

- 1. MOBILE POS/RETAIL**
- 2. PARKING LOT**
- 3. LOGISTICS**
- 4. SHIP TRANSPORT**
- 5. ON-SITE REPAIR/INSTALLATION**
- 6. WAREHOUSE/REAR SERVICE**
- 7. UTILITY BILLING/METER READING**



Portable Printer MODEL : NWE PTP II		
ITEM		Parameter
Printing	Printing method	Thermal printing
	Resolution	203dpi, 8dots/mm,
	Printing speed	50mm/s to 90 mm/s
	Valid printing width	48 mm
	Interface	Bluetooth (Windows ,Android / IOS), Type-c
Power saving	Sleep mode	YES
Character Set	Font	ASCII:9×17,12×24; Multiple code pages support
Barcode Symbolizes	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, Aztec, Data Matrix, GS1 Data bar, Maxi Code,PDF417
Graphics		Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max. 64K for total)
Detection	Sensors	Paper out detection
LED indicator	Error	Red
	Status	Blue
	Power / Charging	Green
	Battery	2600mAh/7.4V rechargeable Li-ion battery
	Paper width	58 mm
	Paper roller diameter	≤50mm
	Paper loading	Easy loading mechanism
Physical characteristics	Working condition	-15°C~50°C , 20%~85%RH
	Storage condition	-30°C~70°C, 5%~95%RH
	Dimension	120*82*60mm
	Weight	197g (without paper roll)
Software	Emulation	ESC/POS compatible command set
	Driver	Windows XP//Win7//Win8//Win10
	Memory	Flash:2 MB & RAM 1 MB
Biometrics Scanner	L1 Biometrics	STQC certified L1 Bio Metrics Scanner